




THD300

Operator working instructions

Developer for Energy Elite Eco.

General information	
Working instructions	
Shelf life	<ul style="list-style-type: none">• 24 months
Storage	<ul style="list-style-type: none">• Average temperature +20°C.• Max. temperature +23°C.• Min. temperature +4°C.• No adjustment of the relative humidity.• An increase of the temperature up to +28°C is permitted for a period of max. 3 consecutive weeks per year.
Ordering information	 <ul style="list-style-type: none">• Art.code 20 L: 40FH1• Art.code 2x200 L: 40SU7
Waste	 <ul style="list-style-type: none">• Collect if possible.• Send to authorized disposal centres.• Follow local and national regulations.
Safety	 <ul style="list-style-type: none">• Read the Material Safety Datasheet (MSDS) before using this product.• Our products are compliant with the legally prescribed controlling directives eg REACH, ISO 9001. We work in partnership with leading printing press manufacturers including Manroland, Heidelberg & KBA. Where applicable Agfa offers fountain additives & washes which are food grade compliant (FOGRA listed). Click here for more information on our SHE policy.

Advised for	
Plates	<ul style="list-style-type: none">• Energy Elite Eco

Properties	
Appearance	<ul style="list-style-type: none">• Colourless
Density	<ul style="list-style-type: none">• 1.037 Kg/L
Conductivity (20°C)	<ul style="list-style-type: none">• 76.0 mS/cm

